

Specshield H₂, Ar

(mixtures containing up to 2.93% hydrogen)

PRODUCT: SPECSHIELD UP TO 2.93% HYDROGEN/ARGON MSDS NR : 300-15-0077 BOC (A) VERSION: 1.01 DATE: 17/08/06 PAGE: 1/2

1 IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND OF THE COMPANY

Product name	Specshield up to 2.93% Hydrogen/Argon
Company identification	see heading and/or footer
Emergency phone Nos	see heading and/or footer

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/ Preparation	Preparation
Components/ Impurities	Contains Hydrogen (F+;R12) (EINECS No. 215-605-7) balance Argon (EINECS No. 231-147-0). Check the cylinder collar for the exact composition.
EEC Nr (from EINECS)	Not applicable for preparations.

3 HAZARDS IDENTIFICATION

In high concentrations may cause asphyxiation.
Compressed gas.
Not classified as dangerous preparation.

4 FIRST AID MEASURES

Inhalation	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Ingestion	Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode. Inform Fire Brigade. Non flammable
Hazardous combustion products	None
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position.
Special protective equipment for fire fighters	In confined space use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions	Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Post warning notices. Ensure adequate air ventilation.
Environmental precautions	Try to stop release. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Clean up methods	Ventilate area.

7 HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Refer to supplier's container handling instructions. Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection	Ensure adequate ventilation.
----------------------------	------------------------------

9 PHYSICAL AND CHEMICAL PROPERTIES

Relative density, gas	Heavier than air.
Solubility mg/l water	Not known.
Appearance/Colour	Colourless gas.
Odour	No odour warning properties.
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. Will displace oxygen when ventilation is at high point only.

10 STABILITY AND REACTIVITY

Stability and reactivity	Stable under normal conditions.
---------------------------------	---------------------------------

11 TOXICOLOGICAL INFORMATION

General	No known toxicological effects from this product.
----------------	---

12 ECOLOGICAL INFORMATION

General	No known ecological damage caused by this product.
----------------	--

SAFETY DATA SHEET

13 DISPOSAL CONSIDERATIONS

General Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.

14 TRANSPORT INFORMATION

Proper Shipping Name Compressed Gas No.5 (Argon Hydrogen)

UN Nr 1956

Class/Div 2.2

ADR/RID Classification Code 1A

ADR/RID Hazard Nr 20

Labelling ADR Label 2.2: non flammable non toxic gas

Other transport information Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers ensure that they are firmly secured and:

- cylinder valve is closed and not leaking
- valve outlet cap nut or plug (where provided) is correctly fitted
- valve protection device (where provided) is correctly fitted
- there is adequate ventilation
- compliance with applicable regulations

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548 Not applicable for preparations.

EC Classification Not classified as dangerous preparation.

Labelling of cylinders - Symbols Label 2.2: non flammable non toxic gas.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Asphyxiant in high concentrations.

Keep container in well ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Users of breathing apparatus must be trained.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Although this shielding gas alone does not exhibit toxic/harmful effects, the fumes generated from a welding process can be hazardous to health.

Always leak check cylinders when first collected, delivered or used using an approved leak detection fluid.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

For further safety information please refer to "Safe Under Pressure" and "Safe handling, storage and transport of industrial gas cylinders", both of which are available from your local BOC outlet.

CYLINDER CHARACTERISTICS

Cylinder Size	Maximum Filled Pressure (Bar)	Approx. Dimensions incl. valve and guard where supplied (mm)	Approx. Gross Weight (Kg)	Manifold Cylinder Pallet (MCP)	Maximum Filled Pressure (Bar)	Approx. Dimensions incl. valve and guard where supplied (mm)	Approx Gross Weight (kg)
N	200	1460 x 230	85	WN	200	1290 x 1810 x 840	1500

NOTE: Not all cylinder and MCP sizes are available at all locations.
OUTLET CONNECTION: 5/8" BSP female right hand cone recessed.



A member of The BOC Group
 The stripe symbol and the word BOC are BOC Group trademarks.
 © The BOC Group 2006

All BOC Safety Data Sheets are available online at www.boc.com/uk/sds

For product and safety enquiries please phone

In the United Kingdom:
0800 111 333
 (local call rate)

In the Republic of Ireland:
1850 333 435

BOC Customer Service Centre
 Priestley Road, Worsley
 Manchester M28 2UT
 Fax: 0800 111 555

BOC Ireland
 P.O. Box 201
 Bluebell, Dublin 12
 Fax: 01 409 1801