

# Safety Data Sheet

Product : **Carbon dioxide**

Page :1/4

MSDS Nr : 300-00-0032BOC(U)

Version : 1.03

Date : 31/07/2000

Replaces version dated : 10/08/1994

## 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name	Carbon dioxide
Chemical formula	CO <sub>2</sub>
Company identification	see heading and/or footer
Emergency phone numbers	see heading and/or footer

## 2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Substance.
Components/Impurities	Contains no other components or impurities which will influence the classification of the product.
CAS Nr	00124-38-9
EC Nr (from EINECS)	204-696-9

## 3 HAZARDS IDENTIFICATION

Hazards identification	Liquefied gas In high concentrations may cause asphyxiation.
------------------------	---

## 4 FIRST AID MEASURES

Inhalation	Low concentrations of CO <sub>2</sub> cause increased respiration and headache. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin/eye contact	In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Immediately flush eyes thoroughly with water for at least 15 minutes.
Ingestion	Obtain medical assistance Ingestion is not considered a potential route of exposure.

## 5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode. Non flammable
Hazardous combustion products	None
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position.
Special protective equipment for fire fighters	Use self-contained breathing apparatus.

## 6 ACCIDENTAL RELEASE MEASURES

Personal precautions	Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation.
----------------------	--

# Safety Data Sheet

Product :  
MSDS Nr : 300-00-0032BOC(U)

**Carbon dioxide**  
Version : 1.03

Page :2/4  
Date : 31/07/2000  
Replaces version dated : 10/08/1994

Environmental precautions      Try to stop release.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods                      Ventilate area.

## 7 HANDLING AND STORAGE

Handling and storage                      Suck back of water into the container must be prevented.  
Do not allow backfeed into the container.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Refer to supplier's container handling instructions.  
Keep container below 50°C in a well ventilated place.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit value for country      UK: Carbon dioxide - LTEL: 5000ppm; STEL: 15000ppm (EH40/2005)  
Personal protection                      Ensure adequate ventilation.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight                          44  
Melting point                                -56.6 °C  
Boiling point                                (sublimation) -78,5 °C  
Critical temperature                      30 °C  
Relative density, gas                      1.52 (air=1)  
Relative density, liquid                    0.82 (water=1)  
Vapour Pressure 20°C                    57.3 bar  
Solubility mg/l water                      2000 mg/l  
Appearance/Colour                      Colourless gas  
Odour    No odour warning properties.  
Other data                                      Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## 10 STABILITY AND REACTIVITY

Stability and reactivity                    Stable under normal conditions.

## 11 TOXICOLOGICAL INFORMATION

General                                        In high concentrations cause rapid circulatory insufficiency. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness.

## 12 ECOLOGICAL INFORMATION

General                                        When discharged in large quantities may contribute to the greenhouse effect.

# Safety Data Sheet

---

Product :	<b>Carbon dioxide</b>	Page :3/4
MSDS Nr : 300-00-0032BOC(U)	Version : 1.03	Date : 31/07/2000
		Replaces version dated : 10/08/1994

---

Global warming factor 1 (CO<sub>2</sub>=1)

---

## 13 DISPOSAL CONSIDERATIONS

General

To atmosphere in a well ventilated place.  
Discharge to atmosphere in large quantities should be avoided.  
Do not discharge into any place where its accumulation could be dangerous.  
Contact supplier if guidance is required.

---

## 14 TRANSPORT INFORMATION

UN Nr	1013
Class	2.2
ADR/RID Classification code	2A
ADR/RID Hazard Nr	20
Labelling ADR	Label 2.2: non flammable non toxic gas
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking - valve outlet cap nut or plug (where provided) is correctly fitted - valve protection device (where provided) is correctly fitted - there is adequate ventilation. - compliance with applicable regulations.

---

## 15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	Not included in Annex I.
EC Classification	Not classified as dangerous preparation.
EC Labelling (Symbols, R&S phrases)	No EC labelling required.
Labelling of cylinders	
-Symbols	Label 2.2: non flammable non toxic gas

---

## 16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Asphyxiant in high concentrations.

Keep container in well ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Contact with liquid may cause cold burns/frost bite.

Users of breathing apparatus must be trained.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

# Safety Data Sheet

Product :

**Carbon dioxide**

Page :4/4

MSDS Nr : 300-00-0032BOC(U)

Version : 1.03

Date : 31/07/2000

Replaces version dated : 10/08/1994

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document.****Number of pages :4**