

Safety Data Sheet

Product :

Propel 70

Page :1/5

MSDS Nr : 302-25-2025BOC(A)

Version : 1

Date : 22/11/2004

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name	Propel 70
Company identification	see heading and/or footer
Emergency phone numbers	see heading and/or footer

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Preparation
Components/Impurities	Contains the following components: 30% Butane n- {F+;R12} {EINECS No. 203-448-7}/15% Isobutane {F+;R12} {EINECS No. 200-857-2}/55% Propane {F+;R12} {EINECS No. 200-827-9}
EC Nr (from EINECS)	Not applicable for preparations

3 HAZARDS IDENTIFICATION

Hazards identification	Extremely flammable Liquefied gas
------------------------	--------------------------------------

4 FIRST AID MEASURES

Inhalation	In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin/eye contact	In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical assistance
Ingestion	Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	Incomplete combustion may form carbon monoxide.
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position.

Safety Data Sheet

Product :

Propel 70

Page :2/5

MSDS Nr : 302-25-2025BOC(A)

Version : 1

Date : 22/11/2004

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.

Special protective equipment for fire fighters

Use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions

Evacuate area.

Ensure adequate air ventilation.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Eliminate ignition sources.

Environmental precautions

Try to stop release.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods

Ventilate area.

Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (Ground free from frost).

7 HANDLING AND STORAGE

Handling and storage

Ensure equipment is adequately earthed.

Suck back of water into the container must be prevented.

Purge air from system before introducing gas.

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Keep away from ignition sources (including static discharges).

Segregate from oxidant gases and other oxidants in store.

Refer to supplier's container handling instructions.

Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit value for country

UK: Butane n - LTEL: 600ppm; STEL: 750ppm (EH40/2005)

UK: Isobutane - LTEL: 600ppm; STEL: 750ppm (EH40/2005)

Personal protection

Ensure adequate ventilation.

Do not smoke while handling product.

Protect eyes, face and skin from liquid splashes.

Safety Data Sheet

Product :

Propel 70

Page :3/5

MSDS Nr : 302-25-2025BOC(A)

Version : 1

Date : 22/11/2004

9 PHYSICAL AND CHEMICAL PROPERTIES

Boiling point	-25 °C
Relative density, gas	1.78 (air=1)
Relative density, liquid	0.536 (water=1)
Vapour Pressure 20°C	4.7 bar
Vapour Pressure Range 70°F	66-74 psig
Solubility mg/l water	No reliable data available.
Appearance/Colour	Colourless liquid
Odour	No odour warning properties.
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity	Can form explosive mixture with air. May react violently with oxidants.
--------------------------	--

11 TOXICOLOGICAL INFORMATION

General	Butane n- - In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Isobutane - In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.
---------	--

12 ECOLOGICAL INFORMATION

General	No known ecological damage caused by this product.
---------	--

13 DISPOSAL CONSIDERATIONS

General	Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
---------	---

14 TRANSPORT INFORMATION

Proper shipping name	HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (Propane, n-Butane)
UN Nr	1965

Safety Data Sheet

Product :

Propel 70

Page :4/5

MSDS Nr : 302-25-2025BOC(A)

Version : 1

Date : 22/11/2004

Class	2
ADR/RID Classification code	2F
ADR/RID Hazard Nr	23
Packing group	None
Labelling ADR	Label 2.1: flammable gas
IMDG EmS codes	F-D, S-U
IMDG Marine pollutant	No
IATA passenger packing instruction	Forbidden
IATA passenger max. quantity/pack	Forbidden
IATA cargo packing instruction	200
IATA cargo max. quantity/pack	150kg
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking - valve outlet cap nut or plug (where provided) is correctly fitted - valve protection device (where provided) is correctly fitted - there is adequate ventilation. - compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	Not applicable for preparations
EC Classification	F+;R12
-Symbols	F+: Extremely flammable
Labelling of cylinders	
-Symbols	Label 2.1: flammable gas
-Risk phrases	R12 Extremely flammable.
-Safety phrases	S9 Keep container in well ventilated place. S16 Keep away from ignition sources - No smoking. S33 Take precautionary measures against static discharges.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.
Ensure operators understand the flammability hazard.

Safety Data Sheet

Product :

Propel 70

Page :5/5

MSDS Nr : 302-25-2025BOC(A)

Version : 1

Date : 22/11/2004

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Contact with liquid may cause cold burns/frost bite.

Users of breathing apparatus must be trained.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document.

Number of pages :5